This drawing a information co					PART NUMBER	LENGTH
herein are the					.120C550SCSSP	55 mm
and proprietar					.120C600SCSSP	60 mm
of Global Supply LLC					.120C650SCSSP	65 mm
					.120C700SCSSP	70 mm
					.120C750SCSSP	75 mm
					.120C800SCSSP	80 mm
					.120C850SCSSP	85 mm
		12 mm			.120C900SCSSP	90 mm
⊢18 m	im -i -	-	xx		.120C950SCSSP	95 mm
			26 mm	Thread Length	.120C1000SCSSP	100 mm
6			36 1111	Thread Length	.120C1100SCSSP	110 mm
10	21		1000		.120C1200SCSSP	120 mm
))			12 mm	.120C1300SCSSP	130 mm
	⊢-10 mm	nex	M12 x 1.75 n	nm Thread —		
NOTES: 1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE	RAWINGS PER AND TOLERAN	DIN 912 STAND CES PER ISO 47	0ARD. 762.	nm Thread -⁄	0	
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE	RAWINGS PER AND TOLERAN	DIN 912 STAND CES PER ISO 47	ØARD. 762. ₽		0	
1. INTERPRET DF 2. DIMENSIONS	RAWINGS PER AND TOLERAN	DIN 912 STAND CES PER ISO 47	0ARD. 762.	DESCRIPTION:	AD CAP SCREW, PARTIALLY THR	
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE	RAWINGS PER AND TOLERAN ACH COMPLIA METRIC X.XXX + X.XX +	DIN 912 STAND CES PER ISO 47	OARD. 762. ■ MATERIAL:	DESCRIPTION:		
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in	RAWINGS PER AND TOLERAN ACH COMPLIA METRIC X.XXX + X.XX +	DIN 912 STANE CES PER ISO 47 NT +/- 0.100 -/- 0.100	DARD. 762. ■ MATERIAL: A2 STAINLESS STEEL FINISH:	DESCRIPTION: M12-1.75 SOCKET HEA	AD CAP SCREW, PARTIALLY THR	
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in millimeters	RAWINGS PER AND TOLERAN ACH COMPLIA METRIC X.XXX + X.XX + X.X +	DIN 912 STANE CES PER ISO 47 NT +/- 0.100 -/- 0.100	DARD. 762. MATERIAL: A2 STAINLESS STEEL FINISH: PASSIVATE FSCM No.	DESCRIPTION: M12-1.75 SOCKET HEA	AD CAP SCREW, PARTIALLY THR	EADED
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: TOLERANCES: Unless specified otherwise, all dimensions are in millimeters DRAWN BY:	RAWINGS PER AND TOLERAN ACH COMPLIA METRIC X.XXX + X.XX + X.X + L CLARY	DIN 912 STANE CES PER ISO 47 NT -/- 0.100 -/- 0.100	OARD. 762. ■ MATERIAL: A2 STAINLESS STEEL FINISH: PASSIVATE	DESCRIPTION: M12-1.75 SOCKET HEA	AD CAP SCREW, PARTIALLY THR .120CXXXSCSSP	EADED
1. INTERPRET DF 2. DIMENSIONS 3. ROHS AND RE DRAWING SCALE: Unless specified otherwise, all dimensions are in millimeters DRAWN BY: REV:	AWINGS PER AND TOLERAN ACH COMPLIA METRIC X.XXX + X.XX + X.XX + X.X + L CLARY APPROVAL	DIN 912 STANE CES PER ISO 47 NT -/- 0.100 -/- 0.100 -/- 0.100 DATE:	DARD. 762. MATERIAL: A2 STAINLESS STEEL FINISH: PASSIVATE FSCM No.	DESCRIPTION: M12-1.75 SOCKET HEA	AD CAP SCREW, PARTIALLY THR	